

According to Regulation (EC) No.1907/2006

## **KEXCELLED HIPS K5**

Product code: Revision Number: Revision date: MSDS No.:

HIPS K5 01 02/12/2022 KS018

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

**Product name:** kexcelled 3D printing filament

Product code: HIPS K5

**Product Use:** A filament to be used in 3D printing applications.

Supplier: NorthBridge New Material Technology(Suzhou) Co.,Ltd

Address: Building# B2, Chaoyang Industrial square, Caohu Industrial

Park, Xiangcheng District, Suzhou. CN.

**Responsible/issuing person:** wilson@northbridge3d.com

**Emergency telephone numbers:** +86-(0512)-65801831

2. HAZARDS IDENTIFICATION

**Health Effects:** Prolonged and /or repeated contacts: Risk of skin

sensitization. When handled at high temperatures, can cause

serious burns.

**Potential Health Effects:** Eye contact: Contact with eyes may cause irritation.

**Skin contact:** Substance may cause slight skin irritation.

**Ingestion:** Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

**Inhalation:** Inhalation of dust may cause shortness of breath, tightness

of the chest, a sore throat and cough. Low hazard for usual

industrial or commercial handling.

Target organ effects: There were no target organ effects noted following

ingestion or dermal exposure in animal studies.



According to Regulation (EC) No.1907/2006

### KEXCELLED HIPS K5

Product code: Revision Number: Revision date: MSDS No.:

HIPS K5 01 02/12/2022 KS018

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name: Olefin Block Copolymers

**CAS Number:** 9003-53-6

Weight: >97%

OSHA Exposure Limits: None

ACGIH Exposure Limits: None

All ingredients in quantities > 1.0% (0.1% for carcinogens) that are potentially hazardous per OSHA definitions.

Other standards: This material can generate Particulates Not Otherwise

Classifiable (PNOC).

The Occupational Safety and Health Administration (OSHA) PEL/TWA for PNOC is 15 mg/m<sup>3</sup> for total dust and 5 mg/m<sup>3</sup> for the respirable fraction. The American Conference of Governmental Industrial Hygienists (ACGIH) TLV/TWA for PNOC is 10 mg/m<sup>3</sup> for inhalable particulates and 3 mg/m<sup>3</sup> for respirable particulates.

### 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air. Call a physician immediately.

**Skin contact:** Rinse immediately with plenty of water for at least 15

minutes. If skin irritation persists, call a physician. Cool skin

rapidly with cold water after contact with hot polymer.

**Eye contact:** Rinse immediately with plenty of water, also under the

eyelids, for at least 15 minutes. Call a physician immediately.

**Ingestion:** Drink water as a precaution. Never give anything by mouth to

an unconscious person. Do not induce vomiting without



According to Regulation (EC) No.1907/2006

## **KEXCELLED HIPS K5**

Product code: Revision Number: Revision date: MSDS No.:

HIPS K5 01 02/12/2022 KS018

medical advice. Call a physician immediately.

**Notes to physician:** Treat symptomatically.

5. FIRE-FIGHTING MEASURES

**Flammable properties:** Autoignition temperature: 588°C.

**Suitable extinguishing media :** Foam. Water. Carbon dioxide (CO2). Dry chemical.

Alcoholresistant foams are preferred if available.

General-purpose synthetic foams (including AFFF) or protein

foams may function, but much less effectively.

Hazardous decomposition: Burning produces obnoxious and toxic fumes Aldehydes

products Carbon monoxide (CO) carbon dioxide (CO2).

**Special protective equipment:** As in any fire, wear self-contained breathing apparatus for

fire fighters pressure demand, MSHA/NIOSH (approved or

equivalent) and full protective gear.

**Under fire conditions:** Cool containers / tanks with spray water. Water mist may

be used to cool closed containers.

Other information: Fine dust dispersed in air may ignite. Risks of ignition

followed by flame propagation or secondary explosions

shall be prevented by avoiding accumulation of dust, e.g. on

floors and ledges.

## **6. ACCIDENTAL RELEASE MEASURES**

Personal precautions: Use personal protective equipment. See Section 8. Remove

all sources of ignition. Avoid dust formation. Avoid contact



According to Regulation (EC) No.1907/2006

## **KEXCELLED HIPS K5**

Product code: Revision Number: Revision date: MSDS No.:

HIPS K5 01 02/12/2022 KS018

with skin and eyes. Sweep up to prevent slipping hazard.

**Environmental precautions:** Do not flush into surface water or sanitary sewer system. Do

not allow material to contaminate ground water system.

Methods for cleaning up: Shovel into suitable container for disposal.

7. HANDLING AND STORAGE

Safe handling advice: Avoid contact with skin and eyes. Workers should be

protected from the possibility of contact with molten

material during fabrication. Low hazard for usual industrial

or commercial handling. Use personal protective

equipment.

**Storage conditions:** Store in cool place. Keep at temperatures below 50°C(122F).

No special restrictions on storage with other products.

**Precautions:** No special precautions required.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Eye/face protection:** Wear safety glasses for general purpose.

**Hand protection:** Wear gloves (product handled in molten state).

**Skin and body protection:** Wear protective clothing (product handled in molten state).

**Respiratory protection:** In case of dust formation, wear a dust mask.

In case of insufficient ventilation, wear suitable respiratory

equipment.

**Hygiene measures:** Avoid contact with skin, eyes, and clothing.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES



According to Regulation (EC) No.1907/2006

## **KEXCELLED HIPS K5**

Product code: Revision Number: Revision date: MSDS No.:

HIPS K5 01 02/12/2022 KS018

**Appearance:** opaque, filaments. Solid at room temperature..

Color: Opaque.

Odour: Sweet .

pH: not applicable.

Vapor pressure: Not determined.

Vapor density: Not determined.

**Evaporation rate:** Not determined.

Density: 1.04g/cm3

**Boilingpoint/range:** Not applicable. Decomposition temperature: 300 °C (572F).

Melting point/range:180 - 260 °C.

Water solubility: Insoluble.

Solubility in other solvents: Noneknown.

## **10. STABILITY AND REACTIVITY**

**Stability:** Stable under recommended storage conditions.

to avoid: Temperatures above 230°C (446F).

Materials to avoid: Oxidizing agents. . Strong bases.

**Decomposition:** Burning produces obnoxious and toxic fumes. Aldehydes.

Carbon monoxide (CO). Carbon dioxide (CO2).

**Polymerization:** Not applicable.

#### 11. TOXICOLOGICAL INFORMATION

See section 3 for potential health effects. For detailed toxicological data, write or call the address or emergency number shown in section 1



According to Regulation (EC) No.1907/2006

### **KEXCELLED HIPS K5**

Product code: Revision Number: Revision date: MSDS No.:

HIPS K5 01 02/12/2022 KS018

### 12. ECOLOGICAL INFORMATION

Mobility: No data available

**Bioaccumulation:** Does not bioaccumulate. Inherently biodegradable

### 13. DISPOSAL CONSIDERATIONS

Controlled incineration or landfill according to local, state or national laws and regulations concerning health and pollution.

#### 14. TRANSPORT INFORMATION

IMDG: Not regulated.

ICAO/IATA: Not regulated.

## **15. REGULATORY INFORMATION**

NOTICE: The information herein is presented in good faith and believed to be accurate as of the print date shown above. However, no warranty, express or implied is given. Regulatory requirements are subject to change and may differ from one location to another; it is the buyer's responsibility to ensure that its activities comply with federal, state or provincial, and local laws.

### **16. OTHER INFORMATION**

The information in this Material Safety Data Sheet (MSDS) is based on current knowledge and experience. No liability can be assumed for the accuracy and completeness of this information.