

According to Regulation (EC) No.1907/2006

KEXCELLED PLA K6

Product code:	Revision Number:	Revision date:	MSDS No.:
PLA K6	03	03/08/2021	KS009

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product name:	kexcelled 3D printing filament
Product code:	PLA K6
Product Use:	A filament to be used in 3D printing applications.
Supplier:	NorthBridge New Material Technology(Suzhou) Co.,Ltd
Address:	Building# B2, Chaoyang Industrial square, Caohu Industrial
	Park, Xiangcheng District, Suzhou. CN.
Responsible/issuing person:	wilson@northbridge3d.com
Emergency telephone numbers:	+86-(0512)-65801831
2. HAZARDS IDENTIFICATION	
Health Effects:	Prolonged and /or repeated contacts: Risk of skin
	sensitization.When handled at high temperatures, can cause
	serious burns.
Potential Health Effects:	Eye contact: Contact with eyes may cause irritation.
Skin contact:	Substance may cause an allergic skin irritation.
Ingestion:	Ingestion may cause gastrointestinal irritation, nausea,
	vomiting and diarrhea.
Inhalation:	Inhalation of dust may cause shortness of breath, tightness
	of the chest, a sore throat and cough. Low hazard for usual
	industrial or commercial handling.
Target organ effects:	There were no target organ effects noted following
	ingestion or dermal exposure in animal studies.



According to Regulation (EC) No.1907/2006

KEXCELLED PLA K6

Product code:	Revision Number:	Revision date:	MSDS No.:		
PLA K6	03	03/08/2021	KS009		
3. COMPOSITION/INFORMATION ON INGREDIENTS					
Chemical name:	Polylactic r	esin			

CAS Number:	9051-89-2
Weight:	>94%
OSHA Exposure Limits:	None
ACGIH Exposure Limits:	None

All ingredients in quantities > 1.0% (0.1% for carcinogens) that are potentially hazardous per OSHA definitions.

```
Other standards:
This material can generate Particulates Not Otherwise

Classifiable (PNOC).
```

The Occupational Safety and Health Administration (OSHA) PEL/TWA for PNOC is 15 mg/m3 for total dust and 5 mg/m3 for the respirable fraction. The American Conference of Governmental Industrial Hygienists (ACGIH) TLV/TWA for PNOC is 10 mg/m3 for inhalable particulates and 3 mg/m3 for respirable particulates.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. Call a physician immediately.
Skin contact:	Rinse immediately with plenty of water for at least 15
	minutes. If skin irritation persists, call a physician. Cool skin
	rapidly with cold water after contact with hot polymer.
Eye contact:	Rinse immediately with plenty of water, also under the
	eyelids, for at least 15 minutes. Call a physician immediately.
Ingestion:	Drink water as a precaution. Never give anything by mouth to
	an unconscious person. Do not induce vomiting without

- 2 -



According to Regulation (EC) No.1907/2006

KEXCELLED PLA K6

Product code:	Revision Number:	Revision date:	MSDS No.:	
PLA K6	03	03/08/2021	KS009	
	medical a	dvice. Call a physician imm	ediately.	
Notes to physician:	Treat sym	Treat symptomatically		
5. FIRE-FIGHTING MEASU	IRES			
Flammable properties:	Autoignit	ion temperature: 388 $^\circ\!\!\mathbb{C}$		
Suitable extinguishing mo	edia : Foam. W	ater. Carbon dioxide (CO2)	. Dry chemical.	
	Alcoholre	esistant foams are preferre	d if available.	
	General-	ourpose synthetic foams (ir	ncluding AFFF) or protein	
	foams ma	ay function, but much less	effectively.	
Hazardous decompositio	n: Burning p	Burning produces obnoxious and toxic fumes Aldehydes		
	products	Carbon monoxide (CO) car	bon dioxide (CO2).	
Special protective equipr	nent: As in any	fire, wear self-contained b	reathing apparatus for	
	fire fighte	ers pressure demand, MSH	A/NIOSH (approved or	
	equivaler	nt) and full protective gear.		
Under fire conditions:	Cool cont	tainers / tanks with spray w	vater. Water mist may be	
	used to c	ool closed containers.		
Other information:	Fine dust	dispersed in air may ignite	. Risks of ignition	
	followed	by flame propagation or se	econdary explosions	
	shall be p	prevented by avoiding accu	mulation of dust, e.g. on	
	floors an	d ledges.		

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:	Use personal protective equipment. See Section 8. Remo	
	all sources of ignition. Avoid dust formation. Avoid contact	



According to Regulation (EC) No.1907/2006

KEXCELLED PLA K6

Product code:	Revision Number	Revision date:	MSDS No.:	
PLA K6	03	03/08/2021	KS009	
	wit	h skin and eyes. Sweep up t	o prevent slipping hazard.	
Environmental precau	utions: Do	not flush into surface wate	r or sanitary sewer system. Do	
	not	not allow material to contaminate ground water system.		
Methods for cleaning	up: Sho	Shovel into suitable container for disposal.		
7. HANDLING AND ST	ORAGE			
Safe handling advice:		id contact with skin and ey	es. Workers should be	
		tected from the possibility	of contact with molten	
		terial during fabrication. Lo	w hazard for usual industrial	
		commercial handling. Use p	ersonal protective	
	equ	ipment.		
Storage conditions:	Sto	re in cool place. Keep at ter	mperatures below 50°C(122F)	
	No	special restrictions on stora	age with other products.	
Precautions:	No	special precautions require	d.	
8. EXPOSURE CONTRO	OLS / PERSONAL PROT	CTION		

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Eye/face protection:	Wear safety glasses for general purpose.
Hand protection:	Wear gloves (product handled in molten state).
Skin and body protection:	Wear protective clothing (product handled in molten state).
Respiratory protection:	In case of dust formation, wear a dust mask.
	In case of insufficient ventilation, wear suitable respiratory
	equipment.
Hygiene measures:	Avoid contact with skin, eyes, and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES



According to Regulation (EC) No.1907/2006

KEXCELLED PLA K6

Product code:	Revision Nur	nber:	Revision date:	MSDS No.:
PLA K6	03		03/08/2021	KS009
Appearance:		opaque, fi	laments. Solid at room ter	nperature.
Color:		Opaque.		
Odour:		Sweet.		
pH:		Not applic	cable.	
Vapor pressure:		Not deter	mined.	
Vapor density:		Not deter	mined.	
Evaporation rate:		Notdeterr	nined.	
Density:		>1.20g/cm	13	
Boilingpoint/range:		Not applie	cable. Decomposition tem	perature: 280 °C (536F).
		Melting p	oint/range:155 – 185 °C.	
Water solubility:		Insoluble.		
Solubility in other solven	ts:	Noneknov	vn.	

10. STABILITY AND REACTIVITY

Stability:	Stable under recommended storage conditions. Conditions
	to avoid:Temperatures above 230°C (446F).
Materials to avoid:	Oxidizing agents. Strong bases.
Decomposition:	Burning produces obnoxious and toxic fumes. Aldehydes.
	Carbon monoxide (CO). Carbon dioxide (CO2).
Polymerization:	Not applicable.

11. TOXICOLOGICAL INFORMATION

See section 3 for potential health effects. For detailed toxicological data, write or call the address or



According to Regulation (EC) No.1907/2006

KEXCELLED PLA K6

Product code:	Revision Number:	Revision date:	MSDS No.:	
PLA K6	03	03/08/2021	KS009	
emergency number show	n in section 1.			
12. ECOLOGICAL INFORM	ATION			
Mobility:	No dat	a available		
Bioaccumulation:	Does not bioaccumulate. Inherently biodegradable			
13. DISPOSAL CONSIDER	ATIONS			
Controlled incineration or	landfill according to lo	ocal, state or national laws and	d regulations concerning	
health and pollution.				
14. TRANSPORT INFORMATION				
IMDG:	Not re	gulated.		
ICAO/ IATA:	Not re	gulated		
15. REGULATORY INFORMATION				
(Not meant to be all inclusive—selected regulations represented).				

NOTICE: The information herein is presented in good faith and believed to be accurate as of the print date shown above. However, no warranty, express or implied is given. Regulatory requirements are subject to change and may differ from one location to another; it is the buyer's responsibility to ensure that its activities comply with federal, state or provincial, and local laws. The following specific information is made for the purpose of complying with numerous federal, state or provincial, and local laws and regulations. See other sections for health and safety information.

WEEE/ROHS DIRECTIVE:	CONFORMS
INVENTORIES:	EINECS (EU): Conforms
TSCA (USA):	Conforms



According to Regulation (EC) No.1907/2006

KEXCELLED PLA K6

Product code:	Revision Number:	Revision date:	MSDS No.:
PLA K6	03	03/08/2021	KS009
DSL (Canada):	Conforms		
AICS (Australia):	Conforms		
ECL (Korea):	Conforms		

16. OTHER INFORMATION

The information in this Material Safety Data Sheet (MSDS) is based on current knowledge and experience. No liability can be assumed for the accuracy and completeness of this information.