

According to Regulation (EC) No.1907/2006

KEXCELLED WOOD K5

Product code:	Revision Number:	Revision date:	MSDS No.:
WOOD K5	03	03/08/2021	KS019

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product name:	kexcelled 3D printing filament
Product code:	WOOD K5
Product Use:	A filament to be used in 3D printing applications.
Supplier:	NorthBridge New Material Technology(Suzhou) Co.,Ltd
Address:	Building# B2, Chaoyang Industrial square, Caohu Industrial
	Park, Xiangcheng District, Suzhou. CN.
Responsible/issuing person:	wilson@northbridge3d.com
Emergency telephone numbers:	+86-(0512)-65801831
2. HAZARDS IDENTIFICATION	
Health Effects:	Prolonged and /or repeated contacts: Risk of skin
	sensitization. When handled at high temperatures, can cause
	serious burns.
Potential Health Effects:	Eye contact: Contact with eyes may cause irritation.
Skin contact:	Substance may cause slight skin irritation.
Ingestion:	Ingestion may cause gastrointestinal irritation, nausea,
	vomiting and diarrhea.
Inhalation:	Inhalation of dust may cause shortness of breath, tightness
	of the chest, a sore throat and cough. Low hazard for usual
	industrial or commercial handling.
Target organ effects:	There were no target organ effects noted following
	ingestion or dermal exposure in animal studies.



According to Regulation (EC) No.1907/2006

KEXCELLED WOOD K5

Product code:	Revision Number:	Revision date:	MSDS No.:
WOOD K5	03	03/08/2021	KS019

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name:	Polylactic resin
CAS Number:	9051-89-2
Weight:	>85%
OSHA Exposure Limits:	None
ACGIH Exposure Limits:	None

All ingredients in quantities > 1.0% (0.1% for carcinogens) that are potentially hazardous per OSHA definitions.

```
Other standards:
This material can generate Particulates Not Otherwise
```

Classifiable (PNOC).

The Occupational Safety and Health Administration (OSHA) PEL/TWA for PNOC is 15 mg/m³ for total dust and 5 mg/m³ for the respirable fraction. The American Conference of Governmental Industrial Hygienists (ACGIH) TLV/TWA for PNOC is 10 mg/m³ for inhalable particulates and 3 mg/m³ for respirable particulates.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. Call a physician immediately.	
Skin contact:	Rinse immediately with plenty of water for at least 15	
	minutes. If skin irritation persists, call a physician. Cool skin	
	rapidly with cold water after contact with hot polymer.	
Eye contact:	Rinse immediately with plenty of water, also under the	
	eyelids, for at least 15 minutes. Call a physician immediately.	
Ingestion:	Drink water as a precaution. Never give anything by mouth to	
	an unconscious person. Do not induce vomiting without	

- 2 -



According to Regulation (EC) No.1907/2006

KEXCELLED WOOD K5

Product code:	Revision Number:	Revision date:	MSDS No.:	
WOOD K5	03	03/08/2021	KS019	
	medical a	dvice. Call a physician imm	ediately.	
Notes to physician:	Treat sym	ptomatically.		
5. FIRE-FIGHTING MEASU	IRES			
Flammable properties:	Autoignit	tion temperature: 588 $^\circ\!\mathrm{C}$.		
Suitable extinguishing m	edia : Foam. W	Foam. Water. Carbon dioxide (CO2). Dry chemical.		
	Alcoholre	esistant foams are preferre	d if available.	
	General-	purpose synthetic foams (in	ncluding AFFF) or protein	
	foams m	ay function, but much less	effectively.	
Hazardous decompositio	n: Burning p	Burning produces obnoxious and toxic fumes Aldehydes		
	products	products Carbon monoxide (CO) carbon dioxide (CO2).		
Special protective equipr	ial protective equipment: As in any fire, wear self-contained breathing appara		reathing apparatus for	
fire fighters		ers pressure demand, MSH	A/NIOSH (approved or	
	equivale	nt) and full protective gear.		
Under fire conditions:	Cool con	tainers / tanks with spray v	vater. Water mist may	
	be used t	co cool closed containers.		
Other information:	Fine dust	dispersed in air may ignite	e. Risks of ignition	
	followed	by flame propagation or se	econdary explosions	
	shall be p	prevented by avoiding accu	mulation of dust, e.g. on	
	floors an	d ledges.		

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:	Use personal protective equipment. See Section 8. Remove	
	all sources of ignition. Avoid dust formation. Avoid contact	



According to Regulation (EC) No.1907/2006

KEXCELLED WOOD K5

Product code:	Revision Nun	nber:	Revision date:	MSDS No.:	
WOOD K5	03		03/08/2021	KS019	
		with skin a	and eyes. Sweep up to pre	vent slipping hazard.	
Environmental precautio	ns:	Do not flu	Do not flush into surface water or sanitary sewer system. Do		
		not allow material to contaminate ground water system.			
Methods for cleaning up	:	Shovel int	o suitable container for di	sposal.	
7. HANDLING AND STOR	AGE				
Safe handling advice:		Avoid contact with skin and eyes. Workers should be			
		protected	protected from the possibility of contact with molten		
		material during fabrication. Low hazard for usual industrial			
		or commercial handling. Use personal protective			
		equipmen	t.		
Storage conditions:		Store in co	ool place. Keep at tempera	atures below 50°C(122F).	
		No special	restrictions on storage wi	ith other products.	
Precautions:		No special	precautions required.		

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Eye/face protection:	Wear safety glasses for general purpose.
Hand protection:	Wear gloves (product handled in molten state).
Skin and body protection:	Wear protective clothing (product handled in molten state).
Respiratory protection:	In case of dust formation, wear a dust mask.
	In case of insufficient ventilation, wear suitable respiratory
	equipment.
Hygiene measures:	Avoid contact with skin, eyes, and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES



According to Regulation (EC) No.1907/2006

KEXCELLED WOOD K5

Product code:	Revision Number:	Revision date:	MSDS No.:
WOOD K5	03	03/08/2021	KS019
Appearance:	opaque	e, filaments. Solid at roo	m temperature
Color:	Opaque	2.	
Odour:	Sweet .		
pH:	not app	licable.	
Vapor pressure:	Not de	ermined.	
Vapor density:	Not de	ermined.	
Evaporation rate:	Not det	Not determined.	
Density:	>1.20g/	>1.20g/cm3	
Boilingpoint/range:	Not ap	Not applicable. Decomposition temperature: 380 °C (716F).	
	Melting	g point/range:145 – 160	°C.
Water solubility:	Insolub	le.	
Solubility in other solven	ts: Noneki	Noneknown.	
10. STABILITY AND REAC	ΓΙνιτγ		
Stability:	Stable	under recommended sto	prage conditions.
to avoid:	Tempe	ratures above 230°C (44	6F).
Materials to avoid:	Oxidizi	ng agents Strong bases	5.
Decomposition:	Burning	g produces obnoxious a	nd toxic fumes. Aldehydes.
	Carbon	monoxide (CO). Carbor	dioxide (CO2).
Polymerization:	Not ap	plicable.	

11. TOXICOLOGICAL INFORMATION

See section 3 for potential health effects. For detailed toxicological data, write or call the address or emergency number shown in section 1



According to Regulation (EC) No.1907/2006

KEXCELLED WOOD K5

Product code:	Revision Number:	Revision date:	MSDS No.:		
WOOD K5	03	03/08/2021	KS019		
12. ECOLOGICAL INFORMATION					
Mobility:	No data available				
Bioaccumulation:	Does not bioaccumulate. Inherently biodegradable				
13. DISPOSAL CONSIDERATIONS					
Controlled incineration or landfill according to local, state or national laws and regulations concerning					
health and pollution.					
14. TRANSPORT INFORMATION					
IMDG:	Not reg	gulated.			

ICAO/IATA: Not regulated.

15. REGULATORY INFORMATION

NOTICE: The information herein is presented in good faith and believed to be accurate as of the print date shown above. However, no warranty, express or implied is given. Regulatory requirements are subject to change and may differ from one location to another; it is the buyer's responsibility to ensure that its activities comply with federal, state or provincial, and local laws.

16. OTHER INFORMATION

The information in this Material Safety Data Sheet (MSDS) is based on current knowledge and experience. No liability can be assumed for the accuracy and completeness of this information.