

According to Regulation (EC) No.1907/2006

KEXCELLED ABS K5

Product code: Revision Number: Revision date: MSDS No.:

ABS K5 04 29/07/2021 KS012

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product name: kexcelled 3D printing filament

Product code: ABS K5

Product Use: A filament to be used in 3D printing applications.

Supplier: NorthBridge New Material Technology(Suzhou) Co.,Ltd

Address: Building# B2, Chaoyang Industrial square, Caohu Industrial

Park, Xiangcheng District, Suzhou. CN.

Responsible/issuing person: wilson@northbridge3d.com

Emergency telephone numbers: +86-(0512)-65801831

2. HAZARDS IDENTIFICATION

Health Effects: Prolonged and /or repeated contacts: Risk of skin

sensitization. When handled at high temperatures, can cause

serious burns.

Potential Health Effects: Eye contact: Contact with eyes may cause irritation.

Skin contact: Substance may cause an allergic skin irritation.

Ingestion: Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

Inhalation: Inhalation of dust may cause shortness of breath, tightness

of the chest, a sore throat and cough. Low hazard for usual

industrial or commercial handling.

Target organ effects: There were no target organ effects noted following

ingestion or dermal exposure in animal studies.



According to Regulation (EC) No.1907/2006

KEXCELLED ABS K5

Product code: Revision Number: Revision date: MSDS No.:

ABS K5 04 29/07/2021 KS012

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name: Acrylonitrile Butadiene Styrene Copolymer

CAS Number: 9003-56-9

Weight: >98%

Other standards: This material can generate Particulates Not Otherwise

Classifiable (PNOC).

4. FIRST AID MEASURES

General advice: First Aid responders should pay attention to self-protection

and use the recommended protective clothing (chemical

resistant gloves, splash protection). If potential for exposure

exists refer to Section 8 for specific personal protective

equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin contact: Wash skin with plenty of water. Seek first aid or medical

attention as needed. If molten material comes in contact

with the skin, do not apply ice but cool under ice water or

running stream of water. DO NOT attempt to remove the

material from skin. Removal could result in severe tissue

damage.

Seek medical attention immediately. Suitable emergency

safety shower facility should be immediately

Eye contact: Flush eyes thoroughly with water for several minutes.

Remove contact lenses after the initial 1-2 minutes and



According to Regulation (EC) No.1907/2006

KEXCELLED ABS K5

Product code: Revision Number: Revision date: MSDS No.:

ABS K5 04 29/07/2021 KS012

continue flushing for several additional minutes. If effects

occur, consult a physician, preferably an ophthalmologist.

Ingestion: If swallowed, seek medical attention. May cause

gastrointestinal blockage. Do not give laxatives. Do not

induce vomiting unless directed to do so by medical

personnel.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water fog or fine spray. Dry chemical fire extinguishers.

Carbon dioxide fire extinguishers. Foam.

Hazardous decomposition: During a fire, smoke may contain the original material in

addition to combustion products of varying composition

which may be toxic and/or irritating. Combustion products

may include and are not limited to: Nitrogen oxides. Carbon

monoxide. Carbon dioxide. Combustion products may

include trace amounts of: Styrene. Hydrogen cyanide.

Special protective equipment: As in Wear positive-pressure self-contained breathing

apparatus (SCBA) and protective fire-fighting clothing

(includes fire-fighting helmet, coat, trousers, boots, and

gloves). If protective equipment is not available or not used,

fight fire from a protected location or safe distance.

Fire-fighting procedures: Keep people away. Isolate fire and deny unnecessary entry.

Soak thoroughly with water to cool and prevent re-ignition.

If material is molten, do not apply direct water stream. Use



According to Regulation (EC) No.1907/2006

KEXCELLED ABS K5

Product code: Revision Number: Revision date: MSDS No.:

ABS K5 04 29/07/2021 KS012

fine water spray or foam. Cool surroundings with water to

localize fire zone. Hand held dry chemical or carbon dioxide

extinguishers may be used for small fires.

Other information: Fine dust dispersed in air may ignite. Risks of ignition

followed by flame propagation or secondary explosions

shall be prevented by avoiding accumulation of dust, e.g. on

floors and ledges.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Use personal protective equipment. See Section 8. Remove

all sources of ignition. Avoid dust formation. Avoid contact

with skin and eyes. Sweep up to prevent slipping hazard.

Environmental precautions: Do not flush into surface water or sanitary sewer system. Do

not allow material to contaminate ground water system.

Methods for cleaning up: Shovel into suitable container for disposal.

7. HANDLING AND STORAGE

Safe handling advice: Avoid contact with skin and eyes. Workers should be

protected from the possibility of contact with molten

material during fabrication. Low hazard for usual industrial

or commercial handling. Use personal protective

equipment.

Storage conditions: Store in cool place.

No special restrictions on storage with other products.



According to Regulation (EC) No.1907/2006

KEXCELLED ABS K5

Product code: Revision Number: Revision date: MSDS No.:

ABS K5 04 29/07/2021 KS012

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits: Not established.

Eye/face protection: Wear safety glasses for general purpose.

Hand protection: Wear gloves (product handled in molten state).

Skin and body protection: Wear protective clothing (product handled in molten state).

Respiratory protection: In case of dust formation, wear a dust mask.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Hygiene measures: Avoid contact with skin, eyes, and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear, translucent, opaque, filament. Solid at room

temperature.

Color: Clear, Translucent, Opaque.

Odour: None

pH: not determined.

Vapor pressure: Not determined.

Evaporation rate: Not determined.

Density: 1.03-1.10g/cm3

Boilingpoint/range: Not applicable.

Water solubility: Insoluble.

Solubility in other solvents: Noneknown.



According to Regulation (EC) No.1907/2006

KEXCELLED ABS K5

Product code: Revision Number: Revision date: MSDS No.:

ABS K5 04 29/07/2021 KS012

10. STABILITY AND REACTIVITY

Reactivity: No dangerous reaction known under conditions of normal

use.

Chemical stability: Stable.

Conditions to avoid: Avoid temperatures above 300 °C. Exposure to

elevated temperatures can cause product to decompose.

Incompatibility: None known.

Hazardous decomposition products: Decomposition products depend upon temperature, air

products supply and the presence of other materials.

Processing mayrelease fumes and other decomposition

products. At temperatures exceeding melt temperatures,

polymer fragments can be released. Fumes can be

irritating.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Ingestion: Very low toxicity if swallowed. Harmful effects not

anticipated from swallowing small amounts. May cause

choking if swallowed.

Inhalation: No adverse effects are anticipated from single exposure to

dust. Vapours released during thermal processing may cause

respiratory irritation. The LC50 has not been determined.

Eye damage/eye irritation: Solid or dust may cause irritation or corneal injury due to

mechanical action. Elevated temperatures may generate



According to Regulation (EC) No.1907/2006

KEXCELLED ABS K5

Product code: Revision Number: Revision date: MSDS No.:

ABS K5 04 29/07/2021 KS012

vapour levels sufficient to cause eye irritation. Effects may

include discomfort and redness.

Skin corrosion/irritation: Prolonged contact is essentially nonirritating to skin.

Mechanical injury only. Under normal processing

conditions, material is heated to elevated temperatures;

contact with the material may cause thermal burns.

12. ECOLOGICAL INFORMATION

Toxicity: Not expected to be acutely toxic, but material in pellet or

bead form may mechanically cause adverse effects if

ingested by waterfowl or aquatic life.

Persistence and Degradability: This water-insoluble polymeric solid is expected to be inert

in the environment. Surface photodegradation is expected

with exposure to sunlight. No appreciable biodegradation is

expected.

Mobility: No data available

13. DISPOSAL CONSIDERATIONS

Controlled incineration or landfill according to local, state or national laws and regulations concerning health and pollution.

14. TRANSPORT INFORMATION

IMDG: Not regulated.

ADR / RID: Not regulated

ADN/ADNR: Not regulated



According to Regulation (EC) No.1907/2006

KEXCELLED ABS K5

Product code: Revision Number: Revision date: MSDS No.:

ABS K5 04 29/07/2021 KS012

IATA-DGR: Not regulated

15. REGULATORY INFORMATION

NOTICE: The information herein is presented in good faith and believed to be accurate as of the print date shown above. However, no warranty, express or implied is given. Regulatory requirements are subject to change and may differ from one location to another; it is the buyer's responsibility to ensure that its activities comply with federal, state or provincial, and local laws.

16. OTHER INFORMATION

The information in this Material Safety Data Sheet (MSDS) is based on current knowledge and experience. No liability can be assumed for the accuracy and completeness of this information.