

According to Regulation (EC) No.1907/2006

## KEXCELLED OBC K7

Product code:	Revision Number:	Revision date:	MSDS No.:
ОВС К7	01	24/11/2022	KS026

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product name:	kexcelled 3D printing filament
Product code:	OBC K7
Product Use:	A filament to be used in 3D printing applications.
Supplier:	NorthBridge New Material Technology(Suzhou) Co.,Ltd
Address:	Building# B2, Chaoyang Industrial square, Caohu Industrial
	Park, Xiangcheng District, Suzhou. CN.
Responsible/issuing person:	wilson@northbridge3d.com
Emergency telephone numbers:	+86-(0512)-65801831
2. HAZARDS IDENTIFICATION	
Health Effects:	Prolonged and /or repeated contacts: Risk of skin
	sensitization. When handled at high temperatures, can cause
	serious burns.
Potential Health Effects:	Eye contact: Contact with eyes may cause irritation.
Skin contact:	Substance may cause slight skin irritation.
Ingestion:	Ingestion may cause gastrointestinal irritation, nausea,
	vomiting and diarrhea.
Inhalation:	Inhalation of dust may cause shortness of breath, tightness
	of the chest, a sore throat and cough. Low hazard for usual
	industrial or commercial handling.
Target organ effects:	There were no target organ effects noted following
	ingestion or dermal exposure in animal studies.



According to Regulation (EC) No.1907/2006

## KEXCELLED OBC K7

Product code:	<b>Revision Number:</b>	Revision date:	MSDS No.:
OBC K7	01	24/11/2022	KS026

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name:	Olefin Block Copolymers
CAS Number:	308070-21-5
Weight:	>95%
OSHA Exposure Limits:	None
ACGIH Exposure Limits:	None

All ingredients in quantities > 1.0% (0.1% for carcinogens) that are potentially hazardous per OSHA definitions.

```
Other standards:
This material can generate Particulates Not Otherwise

Classifiable (PNOC).
```

The Occupational Safety and Health Administration (OSHA) PEL/TWA for PNOC is 15 mg/m<sup>3</sup> for total dust and 5 mg/m<sup>3</sup> for the respirable fraction. The American Conference of Governmental Industrial Hygienists (ACGIH) TLV/TWA for PNOC is 10 mg/m<sup>3</sup> for inhalable particulates and 3 mg/m<sup>3</sup> for respirable particulates.

#### 4. FIRST AID MEASURES

Inhalation:	Move to fresh air. Call a physician immediately.
Skin contact:	Rinse immediately with plenty of water for at least 15
	minutes. If skin irritation persists, call a physician. Cool skin
	rapidly with cold water after contact with hot polymer.
Eye contact:	Rinse immediately with plenty of water, also under the
	eyelids, for at least 15 minutes. Call a physician immediately.
Ingestion:	Drink water as a precaution. Never give anything by mouth to
	an unconscious person. Do not induce vomiting without

- 2 -



According to Regulation (EC) No.1907/2006

# KEXCELLED OBC K7

Product code:	<b>Revision Number:</b>	Revision date:	MSDS No.:		
OBC K7	01	24/11/2022	KS026		
	medical ad	dvice. Call a physician imm	ediately.		
Notes to physician:	Treat sym	ptomatically.			
5. FIRE-FIGHTING MEASURES					
Flammable properties: Au		Autoignition temperature: 588 $^\circ\!\mathrm{C}$ .			
Suitable extinguishing m	ble extinguishing media : Foam. Water. Carbon dioxide (CO2). Dry chemical.		. Dry chemical.		
	Alcoholre	esistant foams are preferre	d if available.		
	General-J	ourpose synthetic foams (ii	ncluding AFFF) or protein		
	foams ma	ay function, but much less	effectively.		
Hazardous decompositio	n: Burning p	Burning produces obnoxious and toxic fumes Aldehydes			
	products	Carbon monoxide (CO) car	bon dioxide (CO2).		
Special protective equipment: As in any fire, wear self-contained breathing appa		reathing apparatus for			
	fire fighte	fire fighters pressure demand, MSHA/NIOSH (approved or			
	equivaler	nt) and full protective gear.			
Under fire conditions:	Cool cont	tainers / tanks with spray v	vater. Water mist may		
	be used t	o cool closed containers.			
Other information:	Fine dust	dispersed in air may ignite	. Risks of ignition		
	followed	by flame propagation or se	econdary explosions		
	shall be p	prevented by avoiding accu	mulation of dust, e.g. on		
	floors and	d ledges.			

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions:	Use personal protective equipment. See Section 8. Remove	
	all sources of ignition. Avoid dust formation. Avoid contact	



According to Regulation (EC) No.1907/2006

# KEXCELLED OBC K7

Product code:	<b>Revision Numbe</b>	r: Revision date:	MSDS No.:	
OBC K7	01	24/11/2022	KS026	
	wi	th skin and eyes. Sweep up t	o prevent slipping hazard.	
Environmental precautions:		not flush into surface water	r or sanitary sewer system. Do	
		not allow material to contaminate ground water system.		
Methods for cleaning	g <b>up:</b> Sh	ovel into suitable container f	for disposal.	
7. HANDLING AND ST	ORAGE			
Safe handling advice:		oid contact with skin and eye	es. Workers should be	
		protected from the possibility of contact with molten		
		material during fabrication. Low hazard for usual industrial		
		or commercial handling. Use personal protective		
	eq	uipment.		
Storage conditions:		ore in cool place. Keep at ter	nperatures below 50°C(122F)	
	No	special restrictions on stora	ge with other products.	
Precautions:	No	special precautions require	d.	

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Eye/face protection:	Wear safety glasses for general purpose.
Hand protection:	Wear gloves (product handled in molten state).
Skin and body protection:	Wear protective clothing (product handled in molten state).
Respiratory protection:	In case of dust formation, wear a dust mask.
	In case of insufficient ventilation, wear suitable respiratory
	equipment.
Hygiene measures:	Avoid contact with skin, eyes, and clothing.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES



According to Regulation (EC) No.1907/2006

# KEXCELLED OBC K7

Product code:	Revision Number:	<b>Revision date:</b>	MSDS No.:	
OBC K7	01	24/11/2022	KS026	
Appearance:	орас	que, filaments. Solid at roo	m temperature	
Color:	Opa	que.		
Odour:	Swee	et .		
pH:	not a	applicable.		
Vapor pressure:	Not	determined.		
Vapor density:	Not	determined.		
Evaporation rate:	Note	Not determined.		
Density:	0.9g	0.9g/cm3		
Boilingpoint/range:	Not	Not applicable. Decomposition temperature: 380 $^\circ$ C (716F)		
	Melt	ting point/range:90 – 160 °	°C.	
Water solubility:	Inso	luble.		
Solubility in other solven	ts: Non	Noneknown.		
10. STABILITY AND REAC	ΓΙνΙΤΥ			
Stability:	Stab	le under recommended st	orage conditions.	
to avoid:	Tem	peratures above 230°C (44	16F).	
Materials to avoid:	Oxid	lizing agents Strong base	S.	
Decomposition:	Burn	ning produces obnoxious a	nd toxic fumes. Aldehydes.	
	Carb	oon monoxide (CO). Carbor	n dioxide (CO2).	
Polymerization:	Not	applicable.		

### **11. TOXICOLOGICAL INFORMATION**

See section 3 for potential health effects. For detailed toxicological data, write or call the address or emergency number shown in section 1



According to Regulation (EC) No.1907/2006

# KEXCELLED OBC K7

Product code:	Revision Number:	Revision date:	MSDS No.:	
OBC K7	01	24/11/2022	KS026	
12. ECOLOGICAL INFORM	ATION			
Mobility:	No data available			
Bioaccumulation:	Does not bioaccumulate. Inherently biodegradable			
13. DISPOSAL CONSIDERATIONS				
Controlled incineration or landfill according to local, state or national laws and regulations concerning				
health and pollution.				
14. TRANSPORT INFORMATION				
IMDG:	Not r	egulated.		

ICAO/IATA: Not regulated.

### **15. REGULATORY INFORMATION**

NOTICE: The information herein is presented in good faith and believed to be accurate as of the print date shown above. However, no warranty, express or implied is given. Regulatory requirements are subject to change and may differ from one location to another; it is the buyer's responsibility to ensure that its activities comply with federal, state or provincial, and local laws.

#### **16. OTHER INFORMATION**

The information in this Material Safety Data Sheet (MSDS) is based on current knowledge and experience. No liability can be assumed for the accuracy and completeness of this information.